



科技提升绿色未来



KLB-B

牵引车

产品简介

- ◎ 手把式操作舒适自如
- ◎ EPS电子助力转向系统能减少操纵力，提高灵敏度，改善转向回正特性，弯道自动减速功能，使用更轻松、安全
- ◎ 立式驱动交流电机，无需更换碳刷，具有更好的坡道启动性能和再生制动功能，能有效的提高电机的工作效率和使用寿命，更加节能。
- ◎ ZAPI控制器、ALBRIGHT接触器、AMP防水电源接插件

可选配置

- ◎ 冷库专用车型
- ◎ 进口蓄电池
- ◎ 大容量蓄电池
- ◎ 锂电
- ◎ 安全护翼

产品参数

		MODEL (型号)	KLB30B	
Performance (性能)	Maximum load capacity (负载能力)		kg	3000
	Maximum lifting height (起升高度)	H1	mm	280
	Service Weight (with battery) (重量含电池)		kg	670
Dimensions (尺寸)	Overall length of frame (整车长度)	L	mm	1467
	Overall width of frame (整车宽度)	B	mm	735
	Handle height(手柄高度)	H	mm	1410
	Min ground clearance (最小离地间隙)	S	mm	30
	Wheelbase (轴距)	Y	mm	1145
	Minimum turning radius (without platform) (不带踏板最小转弯半径)	Wa	mm	1370
	Minimum turning radius (with platform) (带踏板最小转弯半径)	Wa1	mm	1880
Tire (轮胎)	Front wheel (承载轮)		mm	180*55
	Drive wheel (驱动轮)		mm	230*75
	Caster wheel (平衡轮)		mm	130*55
	Wheel material (车轮类型)	Polyurethane(聚氨酯)		
Electrical components (动力形式)	Drive motor type (驱动电机类型)	AC series motor (交流电机)		
	Rated output (功率)		kw	1.5
battery (电池)	Voltage (电压)		V	24
	Capacity (容量)		AH	210
	Weight (重量)		kg	195

二维线图

