



科技提升绿色未来



KLT电动托盘搬运车



适用于单面 / 双面托盘

产品特点

产品简介

- ◎ EPS电子助力转向系统能减少操纵力，提高灵敏度，改善转向回正特性，弯道自动减速功能，使用更轻松、安全
- ◎ 立式驱动交流电机，无需更换碳刷，具有更好的坡道启动性能和再生制动功能，能有效的提高电机的工作效率和使用寿命，更加节能
- ◎ ZAPI控制器、ALBRIGHT接触器、AMP防水电源接插件
- ◎ 独特的驱动减震技术，叉车通过性能更优越
- ◎ 采用双油缸同步起升，最大高度自动断电功能
- ◎ 带减震的踏板站立式驾驶

可选配置

- ◎ 冷库专用型
- ◎ 非标准货叉
- ◎ 大容量蓄电池 300AH
- ◎ 圈型材专用搬运车定制
- ◎ 可拆卸式安全护翼
- ◎ 锂电

产品参数

		MODEL (型号)			KLT20	KLT25	KLT30
Performance (性能)	Maximum load capacity (负载能力)		kg	2000	2500	3000	
	load center (载荷中心距)	Q	mm	600	600	600	
	Maximum lifting height (起升高度)	H3	mm	120	120	120	
	Travel speed (without load) (无负载行驶速度)		km/h	5.5	5.5	5.5	
	Travel speed (with load) (负载行驶速度)		km/h	5	5	5	
	Lifting speed (without load) (无负载起升速度)		mm/s	50	50	50	
	Lifting speed (with load) (负载起升速度)		mm/s	30	30	30	
	Lowering speed (without load) (无负载下降速度)		mm/s	57	57	57	
	Lowering speed (with load) (负载下降速度)		mm/s	57	57	57	
	Gradeability (without load) (无负载最大爬坡能力)		%	7	7	7	
	Gradeability (with load) (负载最大爬坡能力)		%	6	6	5	
Dimensions (尺寸)	Service Weight (with battery) (重量含电池)		kg	685	685	685	
	Overall length of frame (整车长度)	L	mm	1775	1775	1775	
	Overall length of frame(with platform)(整车长度带踏板)		mm	2280	2280	2280	
	Overall width of frame (整车宽度)	B	mm	735	735	735	
	Wheelbase (轴距)	Y	mm	1417	1417	1417	
	Fork length (货叉长度)		mm	1150	1150	1150	
	Fork outside width (货叉外侧宽度)	B1	mm	685	685	685	
	Fork inside width (货叉内侧宽度)	B2	mm	345	345	345	
	Fork thickness (货叉厚度)		mm	60	60	60	
	Fork height when fork lowered to lowest (货叉降至最低高度)	S	mm	85	85	85	
	Min ground clearance(最小离地间隙)		mm	5	5	5	
	Theoretical width of minimum aisle for right-angle stacking (1200x1000) (直角堆垛通道最小理论宽度)	Asts	mm	2312	2312	2312	
	Minimum turning radius (without platform) (不带踏板最小转弯半径)	Wa	mm	1625	1625	1625	
	Minimum turning radius (with platform) (带踏板最小转弯半径)	Wa1	mm	2135	2135	2135	
Tire (轮胎)	Front wheel (承载轮)		mm	85*70	85*70	85*70	
	Drive wheel (驱动轮)		mm	230*75	230*75	230*75	
	Caster wheel (平衡轮)		mm	130*55	130*55	130*55	
	Wheel material (车轮类型)			polyurethane (聚氨酯)			
Electrical components (动力形式)	Drive motor type (驱动电机类型)			AC series motor (交流电机)			
	Rated output (功率)		kw	1.5	1.5	1.5	
	Hoist motor type (起升电机类型)			DC series motor (直流电机)			
	Rated output (功率)		kw	0.8	1.2	1.2	
battery (电池)	Voltage (电压)		V	24			
	Capacity (容量)		AH	210			
	Weight (重量)		kg	195			

二维线图

